

RC2-B Specificaiton

MODEL	COMPRESSOR				MOTOR						Lubricant charge	Oil		Hydrostatic Pressure Test	WEIGHT	
	Displacem ent 60 / 50Hz	Rated Speed	VI	Cap. Control (%)		Type	Nominal Hp		Starti ng	Voltage (V)		Insulation	Protectio n			Heater
	m <sup>3</sup> /hr	60 / 50Hz		STEP	STEPLE SS		60H z	50H z		60H z	50H z			L	W	Kg/cm2G
RC2-100B	118/98	3550/2950	2.2 2.6 3.0 3.5 4.8	33, 66, 100	33~100	3 Phase, 2 Pole, Squirrel Cage, Induction Motor	38	31	Y-△ PWS DOL	208 220 230 380 440 460 480 575	Class F	PTC Protection	7	150/300	42	280
RC2-140B	165/137			33, 66, 100	33~100		50	41					7			285
RC2-170B	207/172			25, 50, 75, 100	25~100		63	52					7			380
RC2-180B	216/180			33, 66, 100	33~100		66	55					7			335
RC2-200B	233/193			25, 50, 75, 100	25~100		70	58					8			425
RC2-230B	277/230			35, 50, 75, 100	35~100		81	67					14			555
RC2-260B	309/257			25, 50, 75, 100	25~100		90	75					14			560
RC2-300B	352/293			25, 50, 75, 100	25~100		107	89					16			600
RC2-310B	371/308			35, 50, 75, 100	35~100		110	91					16			580
RC2-320B	384/320			25, 50, 75, 100	25~100		114	94					16			600
RC2-340B	407/339			35, 50, 75, 100	35~100		121	101	16	620						
RC2-370B	440/366			35, 50, 75, 100	35~100		130	108	16	640						
RC2-410B	490/407			25, 50, 75, 100	25~100		146	121	15	740						
RC2-470B	567/471			25, 50, 75, 100	25~100		170	141	18	810						
RC2-510B	611/508			35, 50, 75, 100	35~100		183	152	20	780						
RC2-550B	660/549			25, 50, 75, 100	25~100		195	162	23	850						
RC2-580B	702/583			35, 50, 75, 100	35~100		210	175	20	840						
RC2-610B	735/611			25, 50, 75, 100	25~100		214	178	23	960						
RC2-620B	745/619			35, 50, 75, 100	35~100		220	183	23	880						
RC2-710B	858/713			35, 50, 75, 100	35~100		250	208	28	1099						
RC2-790B	952/791	30, 50, 75, 100	30~100	276	230	28	1180									
RC2-830B	993/825	30, 50, 75, 100	30~100	290	234	28	1215									
RC2-930B	1117/929	35, 50, 75, 100	35~100	334	278	28	1240									
RC2-1090B	1310/1089	35, 50, 75, 100	35~100	402	335	---	1430									
RC2-1280B	1535/1276	30, 50, 75, 100	30~100	471	392	---	1580									
RC2-1520B	1832/1523	25, 50, 75, 100	25~100	534	443	---	1630									