



No.	Name	Note	No.	Name	Note
1	Angle valve	1/4"Flare	17	Refrigerant Service Valve	1/4"Flare
2	Discharge flange	2"	18	Connector	1/4"Flare
3	Solenoid valve	50%(NC)	19	Liquid Injection connector	5/8"Flare, option
4	Solenoid valve	75%(NC)	20	Suction flange	3"
5	Solenoid valve	25%(NC)	21	Cable box	Standard
6	Liquid(oil or refrigerant) injection connector	1/4"Flare, option	22	Service flange	
7	Capillary		23	Oil drain valve	option
8	Check valve	2"	24	Oil level switch	option
9	Oil sight glass	Low side	25	Discharge temp. sensor	110°C
10	Oil heater	150W/300W	26	Safety Valve	option
11	Oil filter cartridge		27	Economizer port	7/8"Flare, solder
12	Oil pressure differential switch	option	28	Oil sight glass	High side
13	Oil cooler connector(out)	option	29	Oil temp. sensor	option
14	Stop pin	option	30	Over flow port	option
15	Oil cooler connector(in)	5/8"Flare, option	31	Solenoid valve	Stepless(NO), option
16	Angle valve	1/4"Flare			

\*All stop valves are optional

RC15,RC15L  
Compressor Outline

