

Technical Data RC2-A

MODEL	COMPRESSOR					MOTOR						Lubricant charge	Oil Heater	Hydrostatic Pressure Test	WEIGHT		
	Displacement 60 / 60Hz	Rated Speed 60 / 60Hz	VI	Cap. Control (%)		Type	Nominal Hp		Starting -Up	Voltage (V)						Insulation	Protection
				STEP	STEPLESS		60Hz	50Hz		60Hz	50Hz						
				L	W		Kg/cm2G	kg									
RC2-100A	118/98			33, 66, 100	33-100	23	19						7			275	
RC2-140A	165/137			33, 66, 100	33-100	32	26						7			280	
RC2-170A	207/172			25, 50, 75, 100	25-100	40	33						7			370	
RC2-180A	216/180			33, 66, 100	33-100	42	36						7			300	
RC2-200A	233/193			25, 50, 75, 100	25-100	45	37			208			8			420	
RC2-230A	277/230			35, 60, 75, 100	35-100	63	44			220			14			640	
RC2-260A	309/267			25, 50, 75, 100	25-100	69	49			230			14			645	
RC2-300A	352/293			25, 50, 75, 100	25-100	87	66	Y-Δ		440			16			890	
RC2-310A	371/308			35, 60, 75, 100	35-100	71	59	PWS		460			16			675	
RC2-320A	384/320			25, 50, 75, 100	25-100	72	60	DOL		480			16			695	
RC2-340A	407/339			35, 60, 75, 100	35-100	77	64			480			16			600	
RC2-370A	440/366		2.2	35, 60, 75, 100	35-100	84	70			480			16	150/300		610	
RC2-410A	490/407		2.6	25, 50, 75, 100	25-100	93	78			480			15			730	
RC2-470A	667/471	3550/2950	3.0	25, 50, 75, 100	25-100	108	90			400			18		42	800	
RC2-510A	611/508		3.5	35, 60, 75, 100	35-100	117	98			415			20			760	
RC2-550A	660/549			25, 50, 75, 100	25-100	126	105						23			820	
RC2-580A	702/583			35, 60, 75, 100	35-100	131	109						20			805	
RC2-610A	735/611			25, 50, 75, 100	25-100	135	113						23			945	
RC2-620A	745/619			35, 60, 75, 100	35-100	137	114			380			23			860	
RC2-710A	858/713			35, 60, 75, 100	35-100	158	131			400			28			1070	
RC2-790A	952/791			30, 50, 75, 100	30-100	175	146			450			28			1140	
RC2-830A	993/825			30, 50, 75, 100	30-100	183	152			480			28			1150	
RC2-930A	1117/929			35, 60, 75, 100	35-100	212	176			575			28			1180	
RC2-1090A	1310/1089			35, 60, 75, 100	35-100	247	205						---			1400	
RC2-1280A	1535/1276			30, 60, 75, 100	30-100	286	238						---			1550	
RC2-1520A	1832/1523			25, 50, 75, 100	25-100	331	275						---			1600	

Technical Data RC2-B

MODEL	COMPRESSOR					MOTOR						Lubricant charge	Oil Heater	Hydrostatic Pressure Test	WEIGHT		
	Displacement 60 / 60Hz	Rated Speed 60 / 60Hz	VI	Cap. Control (%)		Type	Nominal Hp		Starting -Up	Voltage (V)						Insulation	Protection
				STEP	STEPLESS		60Hz	50Hz		60Hz	50Hz						
				L	W		Kg/cm2G	kg									
RC2-100B	118/98			33, 66, 100	33-100	38	31						7			280	
RC2-140B	165/137			33, 66, 100	33-100	50	41						7			285	
RC2-170B	207/172			25, 50, 75, 100	25-100	63	52						7			380	
RC2-180B	216/180			33, 66, 100	33-100	66	55						7			335	
RC2-200B	233/193			25, 50, 75, 100	25-100	70	58			208			8			425	
RC2-230B	277/230			35, 60, 75, 100	35-100	81	67	Y-Δ		220			14			655	
RC2-260B	309/267			25, 50, 75, 100	25-100	90	75	PWS		230			14			660	
RC2-300B	352/293			25, 50, 75, 100	25-100	107	89	DOL		280			16			600	
RC2-310B	371/308			35, 60, 75, 100	35-100	110	91			220			16			580	
RC2-320B	384/320			25, 50, 75, 100	25-100	114	94			230			16			600	
RC2-340B	407/339			35, 60, 75, 100	35-100	121	101			280			16			620	
RC2-370B	440/366		2.2	35, 60, 75, 100	35-100	130	108			280			16	150/300		640	
RC2-410B	490/407		2.6	25, 50, 75, 100	25-100	146	121			280			15			740	
RC2-470B	667/471	3550/2950	3.0	25, 50, 75, 100	25-100	170	141			400			18		42	810	
RC2-510B	611/508		3.5	35, 60, 75, 100	35-100	183	152			415			20			780	
RC2-550B	660/549			25, 50, 75, 100	25-100	195	162						23			850	
RC2-580B	702/583			35, 60, 75, 100	35-100	210	175						20			840	
RC2-610B	735/611			25, 50, 75, 100	25-100	214	178						23			960	
RC2-620B	745/619			35, 60, 75, 100	35-100	220	183			380			23			880	
RC2-710B	858/713			35, 60, 75, 100	35-100	250	208			440			28			1100	
RC2-790B	952/791			30, 50, 75, 100	30-100	275	230			460			28			1180	
RC2-830B	993/825			30, 50, 75, 100	30-100	290	234			480			28			1215	
RC2-930B	1117/929			35, 60, 75, 100	35-100	334	278			575			28			1240	
RC2-1090B	1310/1089			35, 60, 75, 100	35-100	402	336						---			1430	
RC2-1280B	1535/1276			30, 60, 75, 100	30-100	471	392						---			1580	
RC2-1520B	1832/1523			25, 50, 75, 100	25-100	534	443						---			1630	